

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> : A61M 25/01		A1	(11) International Publication Number: WO 00/16843
		(43) International Publication Date:	30 March 2000 (30.03.00)
(21) International Application Number: PCT/DK99/00501 (22) International Filing Date: 23 September 1999 (23.09.99) (30) Priority Data: PA 1998 01196 23 September 1998 (23.09.98) DK (71) Applicant (for all designated States except US): COLOPLAST A/S [DK/DK]; Høltedam 1, DK-3050 Humlebaek (DK). (72) Inventors; and (75) Inventors/Applicants (for US only): HANSEN, Henrik, Christian [DK/DK]; Smedebakken 24, DK-2990 Nivaa (DK). TANGHØJ, Allan [DK/DK]; Jølleroed Have 59, DK-2980 Kokkedal (DK). HORSBOEL, Niels [DK/DK]; Torvet 4D, st., DK-3400 Hilleroed (DK). (74) Common Representative: COLOPLAST A/S; Nilausen, Kim, Patent Dept., Høltedam 1, DK-3050 Humlebaek (DK).		(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	
(54) Title: CATHETER SET			
(57) Abstract			
<p>A catheter set comprising a catheter and a package for storing of the catheter before use and for collecting or discharging urine, wherein an elongated part of the package forms a tube and wherein the catheter has a proximal part to be inserted into the urethra, a distal part in the form of a tubular section having an inner diameter at least as large as the inner diameter of the part of the proximal part of the catheter and a sealing part separating the proximal part of the catheter and the tubular distal part. The inventive shape of the catheter combined with the shape of the package prevents a blocking of the free flow of urine from the urethra into the package.</p>			

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon	KR	Republic of Korea	PL	Poland		
CN	China	KZ	Kazakhstan	PT	Portugal		
CU	Cuba	LC	Saint Lucia	RO	Romania		
CZ	Czech Republic	LI	Liechtenstein	RU	Russian Federation		
DE	Germany	LK	Sri Lanka	SD	Sudan		
DK	Denmark	LR	Liberia	SE	Sweden		
EE	Estonia			SG	Singapore		

**TITLE**

Catheter set.

**FIELD OF THE INVENTION**

The present invention relates to a catheter set comprising a catheter and a  
5 package for both storing of the catheter before use and for collecting or  
discharging urine.

**BACKGROUND OF THE INVENTION**

Urinary catheter sets comprising a catheter having a hydrophilic coating, a  
wetting receptacle and a wetting fluid are disclosed in WO publication No.  
10 98/11932 (Coloplast A/S) and in WO publication no. 97/26937 (Astra Aktiebolag).

Both publications describe catheter sets comprising both a catheter and a  
package, and in both publications an elongated part of the package forms a tube  
and is used for leading urine either to the inside of the package for later disposal  
or to an exterior container e.g. a toilet bowl for immediate disposal.

15 The use of such catheter sets is described by referring to figure 1 of WO  
97/26937. First the proximal portion of the pocket 2 is torn off and the elongate  
shaft 18 of the catheter 3 is manoeuvred through the opening in the proximal end  
of the pocket 2 and into the urethra of the patient until a flared distal portion 16  
forms a mechanical seal connection with the opening. Urine in the bladder of the  
20 patient is transported through the lumen of the catheter 3 into the urine collection  
chamber 12. After emptying the bladder the catheter 3 is manoeuvred back  
inside the bag 1 and the open end of the pocket 2 closed off for example by tying  
a knot with the material defining the pocket 2 or clamping the pocket with a  
clamp.

25 A disadvantage with these catheter sets is that the mechanical seal connection  
between the flared distal portion of the catheter and the proximal part of the  
package does not always work properly and the result is that urine flows  
backward and out of the package, especially due to restriction of the flow from

the catheter into the receptacle due to folding, twisting or kinking of the elongate part of the device leading from the catheter to the receptacle..

GB 2031735 discloses a catheter set comprising a catheter within a package for collecting urine. So does GB 2284764, GB 2033231 and US 5147341. The  
5 rearward end of these catheters are either flared outwardly or provided with an arresting member to keep the catheter from leaving the package unintendedly. Non of these references provides an elongated part of the package to serve as a wetting receptacle for wetting the catheter.

US 2856932 discloses a catheter set comprising a catheter and a package  
10 having an elongated part covering part of the catheter to assist insertion of the catheter in a non-contaminating manner. At the rearward end of the catheter it is flared outwardly to keep the catheter in place in relation to the package during use. This shape of entrance into the package provides the same disadvantages and risks of flow restriction as mentioned above due to possible occurrence of  
15 twisting or kinking at the link between the elongated and the broader part of the package. Furthermore a considerable length of the catheter is "inactivated" by not being able to leave the elongated neck and such extra length would have to be added to the catheter in addition to the necessary "active length" causing considerable extra costs. For short catheters this extra length constitutes a  
20 considerable part of the total length of the catheter.

The object of the invention is to solve this problem and provide a catheter set preventing the risk of spilling urine over cloth or surroundings when performing intermitting catheterisation, especially when performed by the patient him- /herself, and at the same time to provide a catheter set which is simple and inexpensive  
25 to produce. It has surprisingly been found that the above drawbacks may be overcome using a catheter set according to the invention.

#### BRIEF DESCRIPTION OF THE INVENTION

The present invention relates to a catheter set comprising a catheter and a package for both storing of the catheter before use and for collecting or  
30 discharging urine. The inventive shape of the catheter combined with the shape

of the package prevents blocking of the free flow of urine from the urethra into the package during use by securing the relatively soft and pliable package from kinking or squeezing.

#### BRIEF DESCRIPTION OF THE DRAWINGS

- 5 The invention will be explained more in detail with reference to the accompanying drawings showing embodiments of the invention and in

Fig. 1 shows an embodiment of a catheter set according to the invention,

Fig. 2 shows the embodiment of Fig. 1 ready for use,

Fig. 3 shows another embodiment of a catheter set according to the invention,

- 10 Fig. 4 shows a sealing system according to the invention in an enlarged scale, and

Fig. 5 shows the embodiment of Fig. 3 in a sealed state.

#### DETAILED DESCRIPTION OF THE INVENTION

- The present invention relates to a catheter set comprising a catheter and a  
15 package for storing of the catheter before use and for collecting or discharging urine, wherein an elongated part of the package forms a tube for accommodating of the catheter. The catheter comprises a proximal part to be inserted into the urethra and a distal part in the form of a tubular section having an inner diameter at least as large as the inner diameter of the part of the proximal part of the  
20 catheter, and a sealing part separating the proximal part of the catheter and the tubular distal part. The length of the tubular distal part is at least long enough to occupy the elongated part of the package.

- The sealing part may e.g. be a part of the catheter having an increased diameter. Such a sealing part will also function as a stop preventing the catheter from  
25 falling out of the package and, at the same time function as a seal during use preventing spilling of urine during catheterisation.

The proximal part of the catheter will usually have an essentially uniform thickness of material as will the distal part.

It is very practical when the sealing part is separating the proximal part of the catheter and the tubular distal part as this provides safety against trying to insert the tubular part into the urethra and also ensures that the tubular part remains in the package for ensuring the free flow of urine into the package.

- 5 When in use, the distal tubular part of the catheter of the invention reaches into the upper part of the package and keeps the front and rear parts thereof apart and thus prevents a blocking of the free flow of urine from the urethra into the package. Thus the length of the tubular distal part of the catheter is at least as long as the length of the elongated part of the package. In the absence of the
- 10 tubular part, urine flowing through the catheter may meet an obstacle if for example the package is folded or squeezed and thus, the urine will fill up the upper part of the package and establish a back pressure on the sealing between the catheter and the package. When a tubular part of the catheter is inside the package as an extension of the catheter it thus prevents the flow of urine from
- 15 being disturbed in the upper part of the relatively soft package, and the flow of urine will be directed downwards until the package is full. The inner diameter of the tubular part of the catheter must be of at least of the same dimension as the proximal part of the in order not to hamper the free flow of urine from the bladder through the catheter and into the package. Thus the inventive shape of the
- 20 catheter in combination with the shape of the package prevents a blocking of the free flow of urine form urethra into the package.

The tubular part of the catheter may be a prolonged part of the catheter itself or a separate tubular piece which is connected to the catheter.

- In a preferred embodiment of the invention the proximal part of the catheter has
- 25 a hydrophilic coating. A hydrophilic coating may be any hydrophilic coating known per se for use for hydrophilic coated catheters and the coating may be applied using any method known per se for applying a hydrophilic coating to a catheter.

- The catheter set according to the invention preferably comprises a wetting fluid
- 30 integrated into the package in order to enable activation of a hydrophilic coating

irrespectively of the access to pure water. The wetting fluid may be sterilised water or saline.

The elongated shape of part of the package is especially useful when the catheter has a hydrophilic coating of the type needing activation by addition of wetting fluid. When the elongated part of the package accommodates the catheter - at least during the wetting process, but preferably already when package is produced and packed ready for sale - the amount of wetting fluid needed to ensure proper wetting is drastically reduced compared to the amount needed if wetting was to take place in the wider part of a package.

- 10 It is understood that the location of the catheter in the elongated part can take place already when the package is produced. But also the package can be produced with the catheter situated inside the broader part of the package in which situation the catheter is introduced into the elongated part of the package at any time prior to use to let the elongated part of the package accommodate the catheter.

In one embodiment of the invention the tubular distal part of the catheter has an inner diameter larger than the inner diameter of the proximal part of the catheter. Thus, no extra resistance against the flow will occur and, as the outer diameter thereof is consequently also greater, the transition between the two parts of the catheter may function as a stop and sealing.

The tubular part of a catheter is preferably made from an extrudable, mouldable material such as a polyolefin such as polyethylene (PE) or polypropylene (PP) or a copolymer of polyethylene such as ethylene vinyl acetate (EVA) or polyvinyl chloride (PVC) or polyvinylidene chloride or a polyurethane (PU) or a silicone. It is envisaged that the proximal and distal tubular part of the catheter and the sealing part may be produced as an integrated unit from the same material by a combination of injection moulding, extrusion and/or blowing.

It is preferred when the tubular distal part of the catheter is transversely corrugated as this adds to the security against kinking. A suitable flexible and

transversely corrugated tube is known per se for preventing blocking by bending of the tube leading to urine collection bags.

In accordance with a preferred embodiment of the catheter set of the invention the package includes an elongated narrow part designed for accommodating the  
5 catheter at least during wetting of the catheter and for the exit of the catheter during use.

In this embodiment the tubular part of the catheter may e.g. be in the form of a telescopically extendible tube having a maximum diameter greater than the proximal part of the catheter. Alternatively the tubular part may be in the form of an  
10 extendible corrugated tubing resembling a corrugated straw which may be folded, compressed or stretched like an accordion. This embodiment can advantageously be used when the urine is led directly to an exterior container e.g. a toilet bowl.

In accordance with another preferred embodiment the package also includes a  
15 broader container part for collecting the urine.

In accordance with yet another preferred embodiment of the invention the package is provided with one or more sealing devices on the exterior side of the package designed for holding and sealing the elongated end of the package after use. When using the package for collecting urine, it is possible to tie a knot  
20 on the elongated part after pushing the catheter into the package but this still leaves a small amount of urine in the outer part of the package which may be spilled onto the clothes which will be embarrassing for the user.

The sealing device is preferably in the form of an adhesive sheet adhered to the package. The sheet may typically comprise a sheet of a relatively soft and pliable  
25 material having an adhesive on the surface facing the outer side of the package and wherein a part of this surface is covered with a release liner which is adhered to the outer surface of the package. Thus, the sheet functions as a part of the surface of the package when not in use, and when used, the sheet is released from the release liner, which is then removed, and the top of the bag is

preferably placed at the adhesive area and the sheet is placed at the adhesive area holding and sealing the end of the bag.

The sealing device of this embodiment securely closes and seals the opening of the package and furthermore, it enables a sealing by bending the top of the  
5 package and securing and sealing the same below a flap of an adhesive sheet adhered to the package the sealing device without having to push the catheter into the package which facilitates the sealing and provides a better security against spilling of urine.

The sheet may be of any suitable material e.g. the ones mentioned above. The  
10 adhesive may be any suitable adhesive being compatible with the package material and the sheet material. It is preferred when the adhesive exhibit some moisture absorbing capability in order to ensure a secure sealing even if some drops of urine are spilled when sealing the top of the package after use. An moisture absorbing adhesive may be any such adhesive known per se for wound  
15 or ostomy purposes, e.g. containing hydrocolloids.

A release liner may for instance be siliconized paper.

The package may be made from a water impervious layer or film of any suitable material known per se for use in the preparation of urine collection bags.

The length of the tubular part may vary according to the specific application. Of  
20 course, it should not be so long that it cannot be comprised in the bag. Even at small lengths of the tubular part an effect is obtained. In a preferred embodiment the tubular part has a length at least corresponding to the narrow upper part of the package.

#### DETAILED DESCRIPTION OF DRAWINGS

25 Reference is made to Fig. 1. The embodiment of the catheter set of the invention shown in Fig.1 comprises a catheter 1, a package 2 for collection of urine, a sealing part 3 and a flexible tubular part 4 connected to the catheter 1. The top of the package is easily torn off at 5 being a weak point for breaking the package. Furthermore, the package comprises another weak point 6 designed for opening

the package at the distal end, if desired, during use, if the package is to function as guide to e.g. a toilet bowl or after use if it is desired to empty the bag immediately. The package is shown with an ear 7 for an easy handling of the package during and after use. Furthermore, a container 8 is shown comprising a wetting  
5 fluid.

In Fig. 2 the embodiment of Fig. 1 is shown after opening the container and wetting the catheter and tearing off the top of the package and pushing the catheter until the stop engages with the bag ready for insertion. The insertion may, if desired, be performed concomitantly with the pushing out of the catheter.

- 10 Especially in the case where the catheter is of the hydrophilic coated type the catheter can be wetted to activate the hydrophilic coating prior to tearing off the top of the package at the weak point 5 and inserting the catheter into urethra. While accommodated in the elongated part of the package the catheter is thus surrounded by the wetting fluid of the container 8 after breaking off the tip of that  
15 container and holding the package so that the elongated part of the package points essentially downwards to ease the transportation of wetting fluid by gravity down into the elongated part of the package.

When the catheter is in use the urine flows in through the openings in the upper part - the proximal end - of the catheter 1 and enters the inside of the package 2  
20 where it passes through the upper part which, in this embodiment, is in the form of a narrow portion as compared to the lower part of the package which is formed as a broader collection part. When the urine is passing the upper part of the package 2 it also passes the flexible tubular part 4 which is present inside this part of the package and secured to the catheter 1. The flexible tube 4  
25 provides the package with a certain stiffness which prevents blocking of this part by kinking or squeezing of the relatively soft and pliable package 2. In the figure the flexible tube is shown as a smooth tube but it might as well have a corrugated surface. The most important features for the tube is that it has to be both bendable and in possession of a certain stiffness.

When the user has finished the use of the catheter he can either throw the used catheter and the filled or urine contaminated package away immediately or he can close the package and transport it to the nearest convenient waste container if there are not any present at the facility.

- 5 The user might experience a problem trying to close the package of the catheter set according to the invention as it is difficult to force the catheter down into the lower part of the package especially when the user has reduced motility of the hands, and when the catheter is still present in the narrow part of the package it is almost impossible for the user to tie a liquid-tight knot on the narrow part as  
10 recommended in the instructions for use of Convene EasiCath Set from Coloplast A/S.

- Reference is made to fig. 3 showing an embodiment of the package of the invention having a sealing device at the exterior side of the package. In order to solve the above problem and render it easier for the user to transport a filled  
15 package it is preferred to use a different kind of closing system as e.g. a system where the upper end of the catheter set package is closed with a piece of gummed tape or tied together by extra added parts.

- A very effective sealing device comprises three pieces of film or paper and is illustrated in figures 3 - 5. Figure 4 shows how the three pieces are arranged in  
20 connection with each other: an upper piece 11, a middle piece 12 and a lower piece 13. The upper piece is non-adhesive on the outer surface and adhesive on the surface facing the package, one end of this piece is adhered to the package and the other end is adhered to the middle piece 12. The middle piece 12 is non-adhesive on both surfaces and both surfaces are made of a material which  
25 makes it possible to release it from adhesive surfaces without spoiling the adhesiveness. The middle piece 12 is preferably considerably larger than the one end of the upper piece 11 it is covering as this makes it easier to grab and remove the middle piece 12 from the package. The middle piece may e.g. be made from siliconised paper. The surface of the middle piece facing 12 away  
30 from the upper piece 11 is facing the lower piece 13. The lower piece 13 is

adhesive on both surfaces, one surface secure the lower piece 13 to the package and the other surface secure the lower piece 13 to the middle piece 12.

- Before the closing device is used for securing and sealing the proximal end of the catheter set, the three pieces are placed on the front or the backside of the package, they are all three releasably glued together as each of them get contact with at least one adhesive surface. When the user need to close the package he pulls the middle piece 12 and the upper end of the upper piece 11 backwards, by this action the middle piece 12 is released from the lower piece 13 (only the movement of the upper piece 11 is indicated in the figure). After the user has remove the middle piece 12 from the upper piece 11, the user places the open end of the catheter set on the lower piece, this will secure the position of the open end, and then the user covers the open end of the package with the upper piece. The open end of the package is now secured between the upper and the lower piece.
- Figure 5 shows a sectional view of a package with the sealing device in a closed position.

**CLAIMS**

1. A catheter set comprising a catheter and a package for storing of the catheter before use and for collecting or discharging urine wherein an elongated part of the package forms a tube for accommodation of the catheter, the catheter  
5 comprises a proximal part to be inserted into the urethra and a sealing part for providing a seal between the catheter and the elongated part of the package during use, CHARACTERISED IN that the catheter further comprises a distal part in the form of a tubular section having an inner diameter at least as large as the inner diameter of the proximal part of the catheter wherein the sealing part  
10 is separating the proximal part of the catheter and the tubular distal part, and wherein the length of the tubular distal part is at least long enough to occupy the elongated part of the package.
2. A catheter set according to claim 1, CHARACTERISED IN that the proximal part of the catheter has a hydrophilic coating.
- 15 3. A catheter set according to claim 1 or 2, CHARACTERISED IN that the set comprises a wetting fluid integrated into the package.
4. A catheter set according to any of claims 1 - 3, CHARACTERISED IN that the tubular distal part of the catheter has an inner diameter larger than the inner diameter of the proximal part of the catheter.
- 20 5. A catheter set according to any of claims 1 - 4, CHARACTERISED IN that the tubular part is made from an extrudable, mouldable material such as a polyolefin such as polyethylene (PE) or polypropylene (PP) or a copolymer of polyethylene such as ethylene vinyl acetate (EVA) or polyvinyl chloride (PVC) or polyvinylidene chloride.
- 25 6. A catheter set according any of claims 1 - 5, CHARACTERISED IN that the tubular distal part of the catheter is transversely corrugated.

- 7 . A catheter set according to any of claims 1 - 6 , CHARACTERISED IN that the package has an elongated narrow part at the end where the catheter exits the package during use and preferably also a broader container part.
- 5 8 . A catheter set according to any of claims 1 - 7 , CHARACTERISED IN that the package is provided with one or more sealing devices on the exterior side of the package.
- 9 . A catheter set according to claim 8 , CHARACTERISED IN that the sealing device comprises an adhesive sheet adhered to the package.

1/4




Fig. 1

2/4




Fig. 2

3/4




Fig. 5




Fig. 3

4/4




FIG. 4

# INTERNATIONAL SEARCH REPORT

International application No.

PCT/DK 99/00501

## A. CLASSIFICATION OF SUBJECT MATTER

IPC7: A61M 25/01

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 9726937 A1 (ASTRA AKTIEBOLAG), 31 July 1997 (31.07.97), page 10, line 1 - line 29; page 11, line 19 - page 12, line 9, figure 1 --	1-5,7
X	WO 9811932 A1 (COLOPLAST A/S), 26 March 1998 (26.03.98), page 14, line 18 - page 15, line 34; page 7, line 13 - line 19, figure 14 --	1-5,7
X	GB 2284764 A (MMG (EUROPE) LTD), 21 June 1995 (21.06.95), page 2, line 47 - page 3, line 15; page 3, line 35 - line 46, figures 1,2, claims 1,2, 8,9, abstract --	1,3-5

☒ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

1 February 2000

Date of mailing of the international search report

18 -02- 2000

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. + 46 8 666 02 86

Authorized officer

Joni Sayeler/AE

Telephone No. + 46 8 782 25 00

# INTERNATIONAL SEARCH REPORT

International application No.

PCT/DK 99/00501

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 2856932 A (J.J. GRIFFITTS), 21 October 1958 (21.10.58), column 1, line 33 - column 2, line 57; column 3, line 16 - line 46, figures 2,7 --	1-9
X	US 5147341 A (STARKE ET AL.), 15 Sept 1992 (15.09.92), column 2, line 43 - column 3, line 7, figure 1 --	1,4,5,7
A	GB 2033231 A (ILLINOIS TOOL WORKS INC.), 21 May 1980 (21.05.80), page 2, line 15 - line 58, figure 1 -- -----	1

# INTERNATIONAL SEARCH REPORT

Information on patent family members

02/12/99

International application No.

PCT/DK 99/00501

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9726937 A1	31/07/97	AU 706432 B	17/06/99
		AU 1562697 A	20/08/97
		AU 2355899 A	24/06/99
		AU 5017596 A	02/10/96
		BR 9707194 A	25/05/99
		CA 2241989 A	31/07/97
		CN 1213976 A	14/04/99
		CZ 9802328 A	16/12/98
		EP 0815663 A	07/01/98
		HU 9901019 A	30/08/99
		IL 125427 D	00/00/00
		JP 11502074 T	16/02/99
		JP 11504249 T	20/04/99
		NO 983406 A	24/09/98
		NZ 326930 A	23/12/98
		PL 327859 A	04/01/99
		SE 9600276 D	00/00/00
		SE 9802435 A	14/09/98
WO 9811932 A1	26/03/98	AU 710581 B	23/09/99
		AU 4295397 A	14/04/98
		CZ 9900917 A	11/08/99
		DK 122496 A	19/03/98
		EP 0923398 A	23/06/99
		NO 991120 A	08/03/99
		PL 332545 A	13/09/99
		AU 710966 B	30/09/99
		AU 4295297 A	29/05/98
		EP 0935478 A	18/08/99
		NO 992029 A	28/04/99
		WO 9819729 A	14/05/98
GB 2284764 A	21/06/95	NONE	
US 2856932 A	21/10/58	NONE	
US 5147341 A	15/09/92	AU 2586492 A	12/04/94
		CA 2126107 A	31/03/94
		EP 0613356 A	07/09/94
		WO 9406377 A	31/03/94
		AU 666129 B	01/02/96

# INTERNATIONAL SEARCH REPORT

Information on patent family members

02/12/99

International application No.

PCT/DK 99/00501

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB 2033231 A	21/05/80	AR 221739 A	13/03/81
		AT 670379 A	15/01/85
		AU 535310 B	15/03/84
		AU 5194679 A	24/04/80
		BE 879467 A	18/04/80
		BR 7906723 A	15/07/80
		CA 1136943 A	07/12/82
		CH 634998 A	15/03/83
		DE 2941336 A	30/04/80
		ES 485218 A	01/10/80
		FR 2446641 A,B	14/08/80
		IT 1123862 B	30/04/86
		IT 7926522 D	00/00/00
		JP 55058169 A	30/04/80
		NL 7907423 A	22/04/80
		NO 146344 B	07/06/82
		NO 150185 B	28/05/84
		NO 793364 A	22/04/80
		NO 820612 A	22/04/80
		NZ 191739 A	25/05/82
		SE 451300 B,C	28/09/87
		SE 7907733 A	09/05/80
		US 4230115 A	28/10/80
		ZA 7905020 A	24/06/81